

SAFETY DATA SHEET

Section 1. Identification

Product name : BARRAGE™ Barium Sulfate Remover

™ a trademark of Baker Hughes Incorporated.

Product code : BARRAGE

Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Intermediate. / Barium Sulfate Remover.

 Print date
 : 1/16/2020

 Validation date
 : 1/16/2020

 Version
 : 1.01

Supplier's details : Baker Petrolite LLC

12645 W. Airport Blvd. Sugar Land, TX 77478

For Product Information/SDSs Call: 800-231-3606

(8:00 a.m. - 5:00 p.m. CST, Monday - Friday) 281-276-5400

Emergency telephone number (with hours of

number (with hours of operation)

: CHEMTREC: 800-424-9300 (U.S. 24 hour) Baker Petrolite: 800-231-3606

(204) 204 270 5400

(001)281-276-5400

CHEMTREC Int'l 01-703-527-3887 (International 24 hour)

Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard

(29 CFR 1910.1200).

Classification of the : SKIN CORROSION - Category 1 SERIOUS EYE DAMAGE - Category 1

TOXIC TO REPRODUCTION (Unborn child) - Category 2

GHS label elements

Hazard pictograms :





Signal word : Danger

Hazard statements : Causes severe skin burns and eye damage. Suspected of damaging the unborn child.

Precautionary statements

Prevention : Øbtain special instructions before use. Do not handle until all safety precautions have

been read and understood. Wear protective gloves. Wear eye or face protection.

Wear protective clothing. Wash hands thoroughly after handling.

Section 2. Hazards identification

Response

: F exposed or concerned: Get medical attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or physician. IF SWALLOWED: Immediately call a POISON CENTER or physician. Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Wash contaminated clothing before reuse. Immediately call a POISON CENTER or physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or physician.

Storage

: Store locked up.

Disposal

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

Hazards not otherwise classified

: None known.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	%	CAS number
Amine acetate salt Potassium oxalate	20 - 30 5 - 10	Trade secret. 583-52-8

Section 4. First aid measures

Description of necessary first aid measures

Eye contact

: Get medical attention immediately. Call a poison center or physician. Immediately flush the eye(s) continuously with lukewarm, gently flowing water for at least 20-60 minutes while holding the eyelid(s) open. Check for and remove any contact lenses. Chemical burns must be treated promptly by a physician.

Inhalation

: Zall a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Skin contact

: Get medical attention immediately. Call a poison center or physician. Wash affected area with soap and mild detergent for at least 20 - 60 minutes. Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Chemical burns must be treated promptly by a physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

Eall a poison center or physician. Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact : Causes serious eye damage.

Inhalation : No known significant effects or critical hazards.

BARRAGE™ Barium Sulfate Remover

Section 4. First aid measures

Skin contact : Causes severe burns.

Ingestion: No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact : pain,watering,redness

Inhalation : reduced fetal weight, increase in fetal deaths, skeletal malformations

Skin contact: pain or irritation,redness,blistering may occur,reduced fetal weight,increase in fetal

deaths, skeletal malformations

Ingestion : stomach pains, reduced fetal weight, increase in fetal deaths, skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments

: No specific treatment.

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing

media

Unsuitable extinguishing media

: None known.

Specific hazards arising from the chemical

Hazardous thermal decomposition products

: In a fire or if heated, a pressure increase will occur and the container may burst.

: carbon dioxide,carbon monoxide,nitrogen oxides,metal oxide/oxides

: Use an extinguishing agent suitable for the surrounding fire.

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

. Fina

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders:

: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Section 6. Accidental release measures

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

If RQ (Reportable Quantity) is exceeded, report to National Spill Response Office at 1-800-424-8802.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Keep away from acids. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, : including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Separate from acids. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
1'	None.

Consult local authorities for acceptable exposure limits.

Section 8. Exposure controls/personal protection

If OSHA permissible exposure levels are shown above they are the OSHA 1989 levels or are from subsequent OSHA regulatory actions. Although the 1989 levels have been vacated the 11th Circuit Court of Appeals, Baker Hughes recommends that these lower exposure levels be observed as reasonable worker protection.

Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before

eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety

showers are close to the workstation location.

Eye/face protection : Wear chemical safety goggles. When transferring material wear face-shield in addition

to chemical safety goggles. If inhalation hazards exist, a full-face respirator may be

required instead.

Hand protection Chemical-resistant gloves.

Skin protection : Wear long sleeves and chemical resistant apron to prevent repeated or prolonged skin

contact.

Respiratory protection : If a risk assessment indicates it is necessary, use a properly fitted, air purifying or

supplied air respirator complying with an approved standard. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the

safe working limits of the selected respirator.

Section 9. Physical and chemical properties

Appearance

Physical state : Liquid. [Clear.] Color : Yellow. [Light] Odor : Odorless. **Odor threshold** : Not available. pН : 12 to 13

: 5% in water

Melting/freezing point : Not available. **Boiling point** : Not available. **Initial Boiling Point** Not available.

Flash point : Closed cup: >94°C (>201.2°F) [TCC]

Burning time : Not applicable. **Burning rate** : Not applicable. **Evaporation rate** : Not available.

Flammability (solid, gas) : Slightly flammable in the presence of the following materials or conditions: open flames,

sparks and static discharge and heat.

Lower and upper explosive

(flammable) limits

: Not available.

Vapor pressure : 2.4 kPa (17.9 mm Hg) @ 21.1°C (Calculated Value for all Components.)

: >1 [Air = 1] Vapor density : 1.2004 (15.6°C) **Relative density Density** : 10 (lbs/gal) Solubility in water : Soluble

BARRAGE™ Barium Sulfate Remover

Section 9. Physical and chemical properties

Partition coefficient: n-

octanol/water

: Not available.

Auto-ignition temperature

: Not available.

Decomposition temperature

: Not available.

Viscosity

: Dynamic (15°C): <50 cP

VOC : Not available.

Pour Point : -4°C (24.8°F)

Section 10. Stability and reactivity

Reactivity: No specific test data related to reactivity available for this product or its ingredients.

Chemical stability: The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : No specific data.

Incompatible materials: Reactive or incompatible with the following materials: oxidizing materials and acids.

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition products should

not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Potassium oxalate	LD50 Oral	Rat	660 mg/kg	-

Irritation/Corrosion

No applicable toxicity data

Sensitization

No applicable toxicity data

Mutagenicity

No applicable toxicity data

Carcinogenicity

No applicable toxicity data

Reproductive toxicity

No applicable toxicity data

Teratogenicity

No applicable toxicity data

Specific target organ toxicity (single exposure)

Not applicable.

Specific target organ toxicity (repeated exposure)

Section 11. Toxicological information

Not applicable.

Aspiration hazard

Not available.

Information on the likely routes of exposure

: Routes of entry anticipated: Dermal, Inhalation.

Potential acute health effects

Eye contact : Causes serious eye damage.

Inhalation : No known significant effects or critical hazards.

Skin contact: Causes severe burns.

Ingestion : No known significant effects or critical hazards.

Potential chronic health effects

General: No known significant effects or critical hazards.Carcinogenicity: No known significant effects or critical hazards.Mutagenicity: No known significant effects or critical hazards.Teratogenicity: Suspected of damaging the unborn child.Developmental effects: No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Dermal	9565.2 mg/kg 15942 mg/kg 48.89 mg/l

Additional information

This product was corrosive when tested using the Corrositex test method.

Section 12. Ecological information

Toxicity

No applicable toxicity data

Persistence and degradability

Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	DOT Classification	TDG Classification	IMDG	IATA
UN number	UN3266	UN3266	UN3266	UN3266
UN proper shipping name	CORROSIVE LIQUID, BASIC, INORGANIC, N. O.S. (Contains: Potassium oxalate, Potassium hydroxide)	CORROSIVE LIQUID, BASIC, INORGANIC, N. O.S. (Contains: Potassium oxalate, Potassium hydroxide)	©ORROSIVE LIQUID, BASIC, INORGANIC, N. O.S. (Contains: Potassium oxalate, Potassium hydroxide)	CORROSIVE LIQUID, BASIC, INORGANIC, N. O.S. (Contains: Potassium oxalate, Potassium hydroxide)
Transport hazard class(es)	8 Commune	8	8	8
Packing group	II	II	II	II
Environmental hazards	No.	No.	No.	No.

Additional information

TDG Classification

: Froduct classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.40-2.42 (Class 8).

IMDG : Emergency schedules F-A S-B

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not available. to Annex II of MARPOL and

the IBC Code

DOT Reportable

Not applicable.

Quantity

Not available. **Marine pollutant**

North-America NAERG : 154

Section 15. Regulatory information

U.S. Federal regulations

: TSCA 12(b) one-time export: No products were found.

TSCA 12(b) annual export notification: No products were found.

United States inventory (TSCA 8b): All components are listed or exempted.

Clean Water Act (CWA) 307: No products were found. Clean Water Act (CWA) 311: Potassium hydroxide

United States - Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs):

List name	Status	Ingredient name	Name on list	Conc.
None of the components are listed.				

SARA 302/304

SARA 311/312

Classification

: Immediate (acute) health hazard Delayed (chronic) health hazard

: No products were found.

: No products were found.

SARA 313

Supplier notification

California Prop. 65

N/A

Canada

Canada (CEPA DSL): : All components are listed or exempted.

Section 16. Other information

National Fire Protection Association (U.S.A.)



History

Date of printing : 1/16/2020

▼ Indicates information that has changed from previously issued version.

Notice to reader

NOTE: The information on this SDS is based on data which is considered to be accurate. Baker Hughes, however, makes no guarantees or warranty, either expressed or implied of the accuracy or completeness of this information.

The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of this product.

This SDS was prepared and is to be used for this product. If the product is used as a component in another product, this SDS information may not be applicable.