**CHAMPIONX** 

SICI10008A

## SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name	:	SICI10008A
Other means of identification	:	Not applicable.
Recommended use	:	CORROSION/SCALE INHIBITOR
Restrictions on use	:	Refer to available product literature or ask your local Sales Representative for restrictions on use and dose limits.
Company	:	ChampionX LLC 11177 S. Stadium Drive Sugar Land, Texas 77478 USA TEL: (281) 632-6500
Emergency telephone number	:	(800) 424-9300 (24 Hours) CHEMTREC
Issuing date	:	09/24/2024

## **SECTION 2. HAZARDS IDENTIFICATION**

## **GHS Classification**

: Danger

## **GHS Label element**

Hazard pictograms

Signal Word

:				
---	--	--	--	--

Hazard Statements : Flammable liquid and vapour. Harmful if swallowed, in contact with skin or if inhale Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage.
--

SICI10008A	
	May cause drowsiness or dizziness. Suspected of damaging fertility or the unborn child. Causes damage to organs (Eyes). May cause damage to organs (Heart, Liver, Kidney) through prolonged or repeated exposure.
Precautionary Statements	<ul> <li>Prevention:         Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Do not breathe dust/fume/gas/mist/vapours/spray. Wear protective gloves/ protective clothing/ eye protection/ face protection.     </li> <li>Response:         IF SWALLOWED: Call a POISON CENTER or doctor/ physician if you feel unwell. Rinse mouth. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.     </li> <li>Storage:         Store in a well-ventilated place.         Dispose of contents/ container to an approved waste disposal plant.     </li> </ul>
Other hazards	: The headspace of containers and manufacturing equipment containing this product may accumulate hydrogen sulfide (H2S) gas. Attach or wear a H2S monitor before opening containers and using or transferring this product. Containers should only be opened in well-ventilated areas. Avoid breathing vapors from the headspace of newly opened containers.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Pure substance/mixture : Mixture

Chemical Name	CAS-No.	<b>Concentration: (%)</b>
Methanol	67-56-1	10 - 30
Amine Triphosphate	Proprietary	5 - 10
Sodium Phosphate, Tribasic	7601-54-9	1 - 5
Quaternary ammonium compounds	Proprietary	1 - 5
2-Mercaptoethanol	60-24-2	1 - 5
Quaternary ammonium compound	Proprietary	1 - 5
Ethylene Glycol	107-21-1	1 - 5

## **SECTION 4. FIRST AID MEASURES**

In case of eye contact	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.
In case of skin contact	:	Wash off immediately with plenty of water for at least 15 minutes. Use a mild soap if available. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention.
If swallowed	:	Rinse mouth. Get medical attention if symptoms occur.

SECTION 5. FIREFIGHTING MEASURES

If inhaled	:	Remove to fresh air. Treat symptomatically. Get medical attention.
Protection of first-aiders	:	In event of emergency assess the danger before taking action. Do not put yourself at risk of injury. If in doubt, contact emergency responders. Use personal protective equipment as required.
Notes to physician	:	Treat symptomatically.
Most important symptoms and effects, both acute and delayed	:	See Section 11 for more detailed information on health effects and symptoms.

Suitable extinguishing media	:	Foam Carbon dioxide Dry powder Other extinguishing agent suitable for Class B fires For large fires, use water spray or fog, thoroughly drenching the burning material.
Unsuitable extinguishing media	:	None known.
Specific hazards during firefighting	:	Fire Hazard Keep away from heat and sources of ignition. Flash back possible over considerable distance. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Hazardous combustion products	:	Carbon oxides nitrogen oxides (NOx) Sulphur oxides Oxides of phosphorus Hydrogen chloride
Special protective equipment for firefighters	:	Use personal protective equipment.
Specific extinguishing methods	:	Use water spray to cool unopened containers. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire and/or explosion do not breathe fumes.

# SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	A respirator and monitor suitable for H2S may be necessary in the event of a spill in a confined area. Ensure adequate ventilation. Remove all sources of ignition. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in sections 7 and 8.
Environmental precautions	:	Do not allow contact with soil, surface or ground water.
Methods and materials for containment and cleaning up	:	Eliminate all ignition sources if safe to do so. Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local /

national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway. Do not flush into surface water or sanitary sewer system.

#### SECTION 7. HANDLING AND STORAGE

Advice on safe handling	:	Hydrogen sulfide gas may accumulate in the headspace of containers during storage. Containers should be opened cautiously and only in well-ventilated areas. Exercise care to avoid exposure to vapors from totes or IBCs when loosening the cap. Use the container bottom valve to perform product transfers. Keep away from fire, sparks and heated surfaces. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Ground and bond container and receiving equipment. Open drum carefully as content may be under pressure. Do not breathe dust, fume, gas, mist, vapours or spray. Do not get in eyes, on skin, or on clothing. Do not ingest. Wash face, hands and any exposed skin thoroughly after handling. Empty product containers may contain product residue. Do not pressurize, cut, heat, weld, or expose containers to flame or other sources of ignition.
Conditions for safe storage	:	Keep away from heat and sources of ignition. Keep in a cool, well-ventilated place. Keep away from oxidizing agents. Keep container tightly closed. Store in suitable labelled containers.
Suitable material	:	The following compatibility data is suggested based on similar product data and/or industry experience: Compatibility with Plastic Materials can vary; we therefore recommend that compatibility is tested prior to use.
Unsuitable material	:	not determined

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Form of exposure	Permissible concentration	Basis
Methanol	67-56-1	TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH
		TWA	200 ppm 260 mg/m3	NIOSH REL
		ST	250 ppm 325 mg/m3	NIOSH REL
		TWA	200 ppm 260 mg/m3	OSHA Z-1
Sodium Phosphate, Tribasic	7601-54-9	STEL	5 mg/m3	US WEEL
2-Mercaptoethanol	60-24-2	TWA	0.2 ppm	US WEEL
Ethylene Glycol	107-21-1	TWA (Vapour.)	25 ppm	ACGIH
		STEL (Vapour.)	50 ppm	ACGIH
		STEL (Inhalable fraction, Aerosol only)	10 mg/m3	ACGIH

Engineering measures

: Effective exhaust ventilation system. Maintain air concentrations below occupational exposure standards.

## Personal protective equipment

Eye protection	:	Safety goggles Face-shield
Hand protection	:	Wear impervious chemical-resistant gloves when handling this product. The following glove types are recommended based on our review of glove manufacturer information and/or other available sources. Impervious gloves, resistant to chemicals. butyl-rubber Other glove types may be used for short term, incidental contact if determined by testing to provide adequate worker protection. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
Skin protection	:	Wear suitable protective clothing.
Respiratory protection	:	Use local exhaust ventilation or other engineering controls as necessary to control airborne vapour and mist. Respiratory protection for hydrogen sulfide is not expected to be necessary in well- ventilated areas. However, if after a thorough hazard assessment respiratory protection is deemed necessary, an appropriate H2S respirator must be used. Use a particulate pre-filter where operations generate significant mists or aerosols. Recommended gas and vapour cartridge: Multi-purpose combination filter. Combined particulates, inorganic and acidic gas/vapour, ammonia/amines and organic vapour type
		pressure, full-facepiece SCBA or supplied-air respirator should be used. Methanol Warning! Protection provided by air purifying respirators is limited due to methanol's ability to break through filter media and its poor warning properties. For prolonged exposures, entry into unknown environments or where methanol is suspected to exceed exposure limits, use a positive pressure, full- facepiece SCBA or supplied-air respirator.
Hygiene measures	:	Handle in accordance with good industrial hygiene and safety practice. Wash face, hands and any exposed skin thoroughly after handling. Remove and wash contaminated clothing before re-use. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

The Personal Protective Equipment (PPE) recommendations provided above have been made in good faith based on typical expected conditions of use. PPE selection should always be completed in conjunction with a proper risk assessment and in accordance with a PPE management program.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES			
Appearance	:	Liquid	
Colour	:	clear	
Odour	:	Pungent	
Flash point	:	31.0 °C, Method: closed cup	

# SICI10008A

рН	:	no data available
Odour Threshold	:	no data available
Melting point/freezing point	:	no data available
Initial boiling point and boiling range	:	no data available
Evaporation rate	:	no data available
Flammability (solid, gas)	:	Not applicable.
Upper explosion limit	:	no data available
Lower explosion limit	:	no data available
Vapour pressure	:	73.9 mm Hg,
Relative vapour density	:	no data available
Relative density	:	1.05, (15.5 °C),
Density	:	8.7 lb/gal
Water solubility	:	completely soluble
Solubility in other solvents	:	no data available
Partition coefficient: n- octanol/water	:	no data available
Auto-ignition temperature	:	no data available
Thermal decomposition	:	no data available
Viscosity, dynamic	:	15.8 mPa.s (-12.2 °C)
		3.7 mPa.s (25 °C)
		7.3 mPa.s (4.4 °C)
Viscosity, kinematic	:	no data available
Molecular weight	:	no data available
VOC	:	no data available

Note: properties listed in this section may be typical, calculated, or estimated values and should not be used as product specifications or for system design. For product specifications see the COA or Technical Data sheet.

SECTION 10. STABILITY AND REACTIVITY				
Reactivity	:	No dangerous reaction known under conditions of normal use.		
Chemical stability	:	Product is stable; however, 2-Mercaptoethanol (2-ME), a component of this product is made from hydrogen sulfide (H2S). 2-ME contains residual H2S and slowly degrades generating additional H2S which can partition from the liquid into the container headspace. Degradation of 2-ME increases with temperature.		
Possibility of hazardous reactions	:	No dangerous reaction known under conditions of normal use.		
Conditions to avoid	:	Heat, flames and sparks.		

E.

SICI10008A		
Incompatible materials	:	Strong oxidizing agents
Hazardous decomposition products	:	Hydrogen sulfide (H2S) In case of fire hazardous decomposition products may be produced such as: Carbon oxides nitrogen oxides (NOx) Sulphur oxides Oxides of phosphorus Hydrogen chloride

# SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of	:	Inhalation, Eye contact, Skin contact
exposure		

## **Potential Health Effects**

Eyes	:	Causes serious eye damage.
Skin	:	May cause allergic skin reaction. Toxic in contact with skin.
		Harmful in contact with skin. Causes skin irritation. May cause allergic skin reaction.
Ingestion	:	Toxic if swallowed. May cause blindness if swallowed.
		May cause blindness if swallowed. Harmful if swallowed.
Inhalation	:	Toxic if inhaled. Inhalation may cause central nervous system effects. Causes headache, drowsiness or other effects to the central nervous system.
		Harmful if inhaled. Inhalation may cause central nervous system effects. Causes headache, drowsiness or other effects to the central nervous system.
Chronic Exposure	:	Suspected of damaging fertility or the unborn child. May cause damage to organs. May cause damage to organs through prolonged or repeated exposure.
Experience with human exp	os	ure
Eye contact	:	Redness, Pain, Corrosion
Skin contact	:	Redness, Irritation, Allergic reactions
Ingestion	:	No information available.
Inhalation	:	Dizziness, Drowsiness
Toxicity		
2		
Product		
·	:	Acute toxicity estimate: 421.18 mg/kg

# SICI10008A

Acute dermal toxicity	:	Acute toxicity estimate: 1,151 mg/kg
Skin corrosion/irritation	:	no data available
Serious eye damage/eye irritation	:	no data available
Respiratory or skin sensitization	:	no data available
Carcinogenicity	:	no data available
Reproductive effects	:	no data available
Germ cell mutagenicity	:	no data available
Teratogenicity	:	no data available
STOT - single exposure	:	no data available
STOT - repeated exposure	:	no data available
Aspiration toxicity	:	no data available

# SECTION 12. ECOLOGICAL INFORMATION

# Toxicity

Environmental Effects :	Very toxic to aquatic life. Harmful to aquatic life with long lasting effects.
Components	
Toxicity to fish :	Methanol LC50: 15,400 mg/l Exposure time: 96 h
	Sodium Phosphate, Tribasic LC50 Oncorhynchus mykiss (rainbow trout): > 100 mg/l Exposure time: 96 h Test substance: Information given is based on data obtained from similar substances.
	2-Mercaptoethanol LC50 Leuciscus idus (Golden orfe): 37 mg/l Exposure time: 96 h
	Ethylene Glycol LC50: 72,860 mg/l Exposure time: 96 h
Components	
Toxicity to daphnia and other : aquatic invertebrates	Methanol EC50 : > 10,000 mg/l Exposure time: 48 h
	Sodium Phosphate, Tribasic EC50 Daphnia magna (Water flea): > 100 mg/l Exposure time: 48 h Test substance: Information given is based on data obtained from similar substances.

	2-Mercaptoethanol EC50 Daphnia magna (Water flea): 0.4 mg/l Exposure time: 48 h
	Quaternary ammonium compound EC50 : 0.0058 mg/l Exposure time: 48 h
	Ethylene Glycol EC50 : > 100 mg/l Exposure time: 48 h
Components	
Toxicity to algae :	Methanol EC50 : 22,000 mg/l Exposure time: 72 h
	Amine Triphosphate EC50 : 550 mg/l Exposure time: 72 h
	Sodium Phosphate, Tribasic EC50 Desmodesmus subspicatus (green algae): > 100 mg/l Exposure time: 72 h Test substance: Information given is based on data obtained from similar substances.
	2-Mercaptoethanol EC50 Desmodesmus subspicatus (Scenedesmus subspicatus): 19 mg/l Exposure time: 72 h
	Ethylene Glycol EC50 : 6,500 mg/l Exposure time: 96 h
Components	
Toxicity to bacteria :	Methanol > 1,000 mg/l
	Ethylene Glycol > 1,995 mg/l
Components	
Toxicity to fish (Chronic : toxicity)	Methanol NOEC: 7,900 mg/l Exposure time: 8.3 d
	Ethylene Glycol NOEC: 15,380 mg/l Exposure time: 7 d
Components	

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: 2-Mercaptoethanol NOEC: 0.063 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea)
	Ethylene Glycol

NOEC: 8,590 mg/l Exposure time: 7 d

#### Persistence and degradability

The organic portion of this preparation is expected to be readily biodegradable.

## Mobility

The environmental fate was estimated using a level III fugacity model embedded in the EPI (estimation program interface) Suite TM, provided by the US EPA. The model assumes a steady state condition between the total input and output. The level III model does not require equilibrium between the defined media. The information provided is intended to give the user a general estimate of the environmental fate of this product under the defined conditions of the models.

If released into the environment this material is expected to distribute to the air, water and soil/sediment in the approximate respective percentages;

Air	: <5%
Water	: 30 - 50%
Soil	: 50 - 70%

The portion in water is expected to be soluble or dispersible.

#### **Bioaccumulative potential**

This preparation or material is not expected to bioaccumulate.

#### Other information

no data available

#### SECTION 13. DISPOSAL CONSIDERATIONS

The information presented only applies to the material as supplied. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated at the time of disposal to determine the proper waste identification and disposal methods in compliance with applicable regulations.

The information presented only applies to the material as supplied. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated at the time of disposal to determine the proper waste identification and disposal methods in compliance with applicable regulations.

Disposal methods	:	The product should not be allowed to enter drains, water courses or the soil. Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste disposal facility.
Disposal considerations	:	Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

## SECTION 14. TRANSPORT INFORMATION

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

The presence of an RQ component (Reportable Quantity for U.S. DOT) in this product causes it to be regulated with an additional description of RQ for road, or as Environmentally hazardous for road and air, ONLY when the net weight in the package exceeds the calculated RQ for the product.

#### Land transport (DOT)

Proper shipping name Technical name(s) UN/ID No. Transport hazard class(es) Packing group Reportable Quantity (per package)	<ul> <li>FLAMMABLE LIQUID, N.O.S.</li> <li>Methanol</li> <li>UN 1993</li> <li>3</li> <li>III</li> <li>25,000 lbs</li> </ul>
package) RQ Component	: Methanol

#### Air transport (IATA)

Proper shipping name	: FLAMMABLE LIQUID, N.O.S.
Technical name(s)	: Methanol
UN/ID No.	: UN 1993
Transport hazard class(es)	: 3
Packing group	: 111
Reportable Quantity (per	: 25,000 lbs
package)	
RQ Component	: Methanol

#### Sea transport (IMDG/IMO)

Proper shipping name	: FLAMMABLE LIQUID, N.O.S.
Technical name(s)	: Methanol
UN/ID No.	: UN 1993
Transport hazard class(es)	: 3
Packing group	: 111
*Marine pollutant	: Quaternary ammonium compounds

\* Note: This product is regulated as a Marine Pollutant when shipped by Rail or Highway (in bulk quantities), and when shipped by water in all quantities.

SECTION 15. REG	JLATORY INFORMATION
TSCA list	: No substances are subject to a Significant New Use Rule.
	No substances are subject to TSCA 12(b) export notification requirements.

#### **EPCRA - Emergency Planning and Community Right-to-Know Act**

#### **CERCLA Reportable Quantity**

## SICI10008A

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)	
Methanol	67-56-1	5000	25000	
SARA 304 Extremely Hazard	ous Substances Re	portable Quantity		
This material does not contain	any components with	a section 304 EHS RQ.		
SARA 311/312 Hazards	Acute toxicity (ar Skin corrosion or Serious eye dam Respiratory or sk Reproductive tox	Flammable (gases, aerosols, liquids, or solids) Acute toxicity (any route of exposure) Skin corrosion or irritation Serious eye damage or eye irritation Respiratory or skin sensitisation Reproductive toxicity Specific target organ toxicity (single or repeated exposure)		
SARA 302	: This material doe EHS TPQ.	es not contain any compon	ents with a section 302	
SARA 313		The following components are subject to reporting levels established by SARA Title III, Section 313:		
	<b>Components</b>	CAS	-No. Weight percent	
	Methanol	67-5	6-1 10 - 30 %	
	Ethylene Glycol	107-	21-1 1 - 5 %	
California Prop. 65	Harm - www.P65Wa	nings.ca.gov		
	Methanol	67-5	6-1	

Methanol	67-56-1
Ethylene Glycol	107-21-1

## INTERNATIONAL CHEMICAL CONTROL LAWS :

#### United States TSCA Inventory

On or in compliance with the active portion of the TSCA inventory.

## Australia. Australian Industrial Chemicals Introduction Scheme (AICIS)

All substances in this product comply with the Australian Industrial Chemicals Introduction Scheme (AICIS)

## **Canadian Domestic Substances List (DSL)**

The substances in this preparation are listed on the Domestic Substances List (DSL), are exempt, or have been reported in accordance with the New Substances Notification Regulations.

## Japan. ENCS - Existing and New Chemical Substances Inventory

On the inventory, or in compliance with the inventory

## Korea. Korean Existing Chemicals Inventory (KECI)

On the inventory, or in compliance with the inventory

## Philippines Inventory of Chemicals and Chemical Substances (PICCS)


On the inventory, or in compliance with the inventory

## **China Inventory of Existing Chemical Substances**

On the inventory, or in compliance with the inventory

Taiwan Chemical Substance Inventory not determined

## SECTION 16. OTHER INFORMATION



REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.